

*a measurable difference...*



## Falling Dart Impact Tester

### Model: F0008

The Falling Dart Impact Tester covers the determination of the energy that causes Polyethylene Film to fail under specified conditions, with the impact of a free-falling dart. This energy is expressed in terms of weight (mass) of the dart falling from a specified height, which would result in 50% failure of specimens tested.

The unit employs a dart, with a 38mm diameter hemispherical head, dropped from a height of 660mm. This unit may be used for films whose impact resistance requires masses of approximately 50gms to 2 kg to fracture them.

### Applications:

- Flexible films

### Features:

- Test Method A: Standard
- Bench-mounted system
- Pneumatic clamping for films
- Brass weighted
- Two Aluminium darts
- Adjustable dart drop height
- Foot Switch for dart release
- Weights supplied: 2x5g, 8x15g, 8x30g, 8x60g

### Options:

- **Test Method B:** Dart Head - 50mm +/- 0.8mm  
Drop Height - 1.50m +/- 0.03m  
Weights supplied - 2x15g, 8x45g, 8x90g
- ASTM D4272: Total Energy Impact of Plastic Films.

The Falling Dart Impact Kinetic energy option, is where the existing F0008 unit is mounted on top of the Kinetic energy option, where there is a catch box and two switches measuring the fall time difference which is displayed on a instrument panel as time.

- Kinetic Energy Option

### Standards:

- ASTM D 1709
- AS/NZS 4347.6
- ISO 7765-1



### Connections:

- **Air Supply:** 60 psi
- **Electrical:** 220/240 VAC @ 50 HZ or  
110 VAC @ 60 HZ  
(please specify when ordering)

### Dimensions:

- **H:** 1,140mm
- **W:** 440mm
- **D:** 500mm
- **Weight:** 30kg

6 Carmen Street, Dandenong, Victoria 3175 Australia.

Phone: +61 3 9706 7837 Fax: +61 3 9706 7249

Web Site: [www.idminstruments.com.au](http://www.idminstruments.com.au) email: [info@idminstruments.com.au](mailto:info@idminstruments.com.au)

All sizes and dimensions shown on this data sheet are averages only and images are as accurate as the medium allows.

Products and details shown may change without notice as IDM Instruments reserves the right to make alterations to its product range from time to time.